1

Description

Communication system, computer comprising a peer-to-peer
message filter and method for processing a peer-to-peer
message

The invention relates to a communication system, a computer
comprising a peer-to-peer message filter and a method for
processing a peer-to-peer message.

It is known that peer-to-peer services are provided by
computers connected to one another by means of a fixed-network
communication network. In pure peer-to-peer services in which
no index-server computer is used, as for example in the case
of the peer-to-peer architecture Gnutella, problems arise in
terms of performance and scaling in the tracing and
distributing of contents to the computers connected to one
another via the fixed-network communication network.

For this reason, in a fixed-network communication network
superpeer computers (also often called "search hubs",
"SuperNodes" or "UltraPeers") have been used which in terms of
their performance, i.e. their computing capacity, and in data
storage as regards the storable volume of data, are superior
to "normal" peer-to-peer computers. The architecture in which
the superpeer computers are used within the framework of peer-
to-peer services is also called a hybrid peer-to-peer computer
architecture.

Within the framework of the hybrid peer-to-peer computer
architecture, it is known for mechanisms to be used, by means
of which a "normal" peer-to-peer computer is selected as a
superpeer computer within a hybrid peer-to-peer service using

the performance data of a peer-to-peer host computer, i.e. of a computer on which a peer-to-peer service is installed. Used as performance data are, for example, the computing capacity of the central processing unit (CPU), the available bandwidth of the communication interface or communication link to which the peer-to-peer computer is connected and the memory space available in the peer-to-peer computer.

According to the prior art, the superpeer computers are available only in the fixed-network communication network. Communication in the fixed-network communication network is normally effected in accordance with the Internet Protocol (IP) and the Transport Control Protocol (TCP) or else the User Datagram Protocol (UDP), as well as in accordance with the peer-to-peer protocol assigned to the peer-to-peer service being used in each case.

If, within the framework of packet-switched communication with a mobile radio terminal, a peer-to-peer service is to be used by the mobile radio terminal, then the performance of a peer-to-peer service used by said mobile radio terminal depends essentially on the point at which a superpeer computer associated with the respective service is disposed within the fixed-network communication network. In peer-to-peer-service data traffic which has been generated by a mobile radio terminal, the data packets of the data traffic must, for example in the case of GPRS (General Packet Radio Service), always be routed via the GGSN computer (gateway GPRS support node computer) until they enter the IP-based fixed-network communication network, and, in the most unfavorable case, return again into a mobile radio communication network.

For this procedure, considerable resources are needed, both in

terms of the computing power of the computers involved and in terms of the available bandwidth of the fixed-network communication network and of the mobile radio communication network, which may possibly result in the impairment of other data traffic or of other voice traffic within the mobile radio communication network.

The fundamental principle of determination and disposal of superpeer computers in a fixed-network communication network is for example known in architectures such as FastTrack or the Gnutella Reflector.

In the case of FastTrack, "normal" peer-to-peer computers are dynamically selected on the basis of their better network connection relative to other peer-to-peer computers, i.e. a greater available bandwidth, or the greater computing capacity available, to be an index-server computer (superpeer computer) for the entire peer-to-peer communication network.

Under the Gnutella architecture, a reflector computer is installed at an input to a generally more poorly connected modem-sub-communication network, which reflector computer bundles inquiries/messages from the rest of the Internet-based communication network transparently for the user and, if possible, replies to them directly. The reflector computer also takes over the buffering of data which is requested very frequently, in other words, of popular content so that the load on peer-to-peer computers which have only a low-rate communication link at their disposal is reduced.

Such a reflector computer is generally installed at network transition points such as, for example, in intranet/Internet gateway computers.

The object of the invention is to improve the availability of
Internet-based peer-to-peer services within a mobile radio
communication network.

The object is achieved in a communication system, a computer
comprising a peer-to-peer message filter, and in a method for
processing a peer-to-peer message having the features
according to the independent claims.

A communication system has a fixed-network communication
network, a mobile radio communication network and a mobile
radio network/fixed network interface computer designed as a
connecting node between these communication networks, which
mobile radio network/fixed network interface computer is
connected to the fixed-network communication network and the
mobile radio communication network, the mobile radio
network/fixed network interface computer being configured as a
GGSN computer (gateway GPRS support node computer). The mobile
radio network/fixed network interface computer is configured
for mapping an incoming data stream from the fixed-network
communication network to the communication protocol used in
the mobile radio communication network and for mapping an
incoming data stream from the mobile radio communication
network to the communication protocol used in the fixed-
network communication network. Furthermore, a superpeer
computer is provided which is connected to the mobile radio
network/fixed network interface computer. Also disposed in the
mobile radio communication network is a peer-to-peer message
filter which is configured such that peer-to-peer messages
supplied from the mobile radio communication network to the
peer-to-peer message filter are detected and supplied to the
superpeer computer. According to one embodiment, it is

provided that communication from the fixed-network
communication network is also effected using the peer-to-peer
message filter, in which case the peer-to-peer message filter
is configured such that peer-to-peer messages supplied from
the fixed-network communication network to the peer-to-peer
message filter are detected and supplied to a computer in the
mobile radio communication network.

A computer comprising a peer-to-peer message filter, which
computer is disposed in the mobile radio communication
network, is configured such that peer-to-peer messages
supplied from a mobile radio communication network to said
computer are detected and can be supplied to a superpeer
computer which is connected to the computer comprising the
peer-to-peer message filter.

In a method for processing a peer-to-peer message, a mobile
radio peer-to-peer message is detected and the mobile radio
peer-to-peer message is transmitted to a superpeer computer
connected to a mobile radio network/fixed network interface
computer and is processed by this superpeer computer. The
detection of the mobile radio peer-to-peer message is effected
according to the invention by means of a computer comprising a
peer-to-peer message filter which is disposed in a mobile
radio communication network.

The invention can clearly be seen as consisting in that
Internet-based peer-to-peer messages are detected in the
mobile radio communication network or at least directly at or
from the point of view of the message flow very near to the
mobile radio communication network and in that they are
forwarded to a superpeer computer disposed very near to the
computer comprising the mobile radio network/fixed network

interface.

The expression "near" is to be understood in this context to
mean that the superpeer computer, i.e. a computer comprising a
superpeer functionality, is connected to the mobile radio
network/fixed network interface computer by means of a
communication link comprising a large available bandwidth, in
other words, by means of an optimized communication link, for
example in the immediate proximity of the mobile radio
network/fixed network interface computer, preferably by means
of a direct connection with no intermediate connection of a
further switching computer, with a dedicated connection to the
Internet-based fixed-network communication network.

The computer comprising a peer-to-peer message filter and
preferably also the superpeer computer are disposed in the
mobile radio communication network and are administered and
operated by the mobile radio communication network operator.

The superpeer computer is preferably disposed in the mobile
radio communication network, where a third-generation mobile
radio network, for example, is used, in the core network of
the mobile radio communication network.

Where a third-generation mobile radio communication protocol
is used, for example in accordance with the GPRS or the UMTS
standard, the superpeer computer is addressable by an SGSN
computer (serving GPRS support node computer) or a GGSN
computer (gateway GPRS support node computer).

According to the invention, the data traffic occurring in the
core network of the mobile radio communication network on the
basis of peer-to-peer messages frequently forwarded via a

plurality of peer-to-peer computers is relieved by the early termination of peer-to-peer data traffic. The early termination can be ascribed in particular to the immediate proximity of the superpeer computer to the mobile radio network/fixed network interface computer.

Furthermore, the support of different peer-to-peer services is optimized in terms of the required bandwidth and the required computing capacity of a superpeer computer.

Furthermore, the response times to peer-to-peer search inquiries/messages are shortened and the requested data is available quickly to the mobile radio terminal requesting the data, as a result of which the quality of service for a user of peer-to-peer services from a mobile communication terminal is improved.

Furthermore, through the selective offer relating to the use of own superpeer computers, the attractiveness and additional earnings opportunities are increased for mobile radio communication network operators.

Preferred further developments of the invention will emerge from the dependent claims.

The embodiments of the invention described hereinbelow relate both to the communication system, to the computer comprising a peer-to-peer message filter and to the method for processing a peer-to-peer message.

According to one embodiment of the invention, the fixed-network communication network is based on Internet protocols, i.e. in particular on the Internet Protocol (IP) and the

Transport Control Protocol (TCP) or else on the User Datagram
Protocol (UDP).

The superpeer computer is preferably disposed in the mobile
radio communication network.

This embodiment of the invention enables the message paths of
peer-to-peer request messages which are sent from a mobile
radio terminal to be further shortened and prevent a situation
whereby a considerable data stream is routed into the fixed-
network communication network, and only after transmission via
a plurality of switching computers and fixed-network peer-to-
peer computers a superpeer computer detected there which can
process the peer-to-peer request messages.

The mobile radio communication network is based according to
one embodiment of the invention on a third- or subsequent-
generation mobile radio system, in particular on one of the
following mobile radio communication networks:
▪ Universal Mobile Telecommunications System (UMTS),
▪ Future Public Land Mobile Telephone System (FPLMTS).

According to another embodiment of the invention, it is
envisaged that the mobile radio communication network be
configured according to the Groupe Speciale Mobile (GSM)
standard.

In the event that a gateway support node computer (GGSN
computer) is provided in the mobile radio network as a mobile
radio network/fixed network interface computer, preferably in
the event that the mobile radio communication network is
configured as a UMTS communication network, communication from

the mobile radio communication network to the fixed-network
communication network and vice versa is effected by means of
the GGSN computer.

According to another embodiment of the invention, an
installation mechanism is provided with which a peer-to-peer
service is installed in the superpeer computer if the
corresponding peer-to-peer service has been requested
sufficiently frequently by mobile radio terminals.

The frequency with which a peer-to-peer service is requested
from a mobile radio terminal can be detected by means of a
counter provided for a respectively offered peer-to-peer
service in the superpeer computer or in the computer
comprising a peer-to-peer message filter. In the event that
the peer-to-peer service has been requested more frequently
than a predetermined threshold provides for, the respective
peer-to-peer service is installed in the superpeer computer,
hereinafter also called a superpeer host computer, unless it
has in any case already been installed in this computer. It
should be noted in this context that multiple superpeers can
be installed on the same superpeer host computer and can
consequently run there.

In an alternative embodiment, it is provided that the
respective counter of the peer-to-peer services be reset after
a predetermined period of time so that a request rate is used
as an installation criterion for the respective peer-to-peer
service, in other words, a peer-to-peer service is installed
in the superpeer computer if, in a predetermined time
interval, more peer-to-peer requests from the mobile radio
terminals in the mobile radio communication network are
requested from the superpeer computer than a predetermined

threshold provides for.

An exemplary embodiment of the invention is shown in the Figure and is explained in detail below.

The Figure shows a communication system 100 comprising a fixed-network communication network 101 and a mobile radio communication network 102.

A plurality of computers 103, 104, 105, 106, 107, 108, 109, 110 are provided in the fixed-network communication network which are connected to one another by means of the fixed-network communication network 101 and which, in accordance with this exemplary embodiment, use the Internet Protocol (IP) and the Transport Control Protocol (TCP) for communication, in other words, the fixed-network communication network 101 is based on Internet protocols.

Furthermore, peer-to-peer services are installed in the fixed-network computers 103, 104, 105, 106, 107 in a freely predeterminable manner and the fixed-network computers 103, 104, 105 are additionally configured for communicating in accordance with the respective peer-to-peer communication protocol so that they can provide and make use of peer-to-peer services.

In the fixed-network computers 103, 104, 105, there are provided, for example, file-sharing services or else services for supplying files, for example multimedia files, especially audio files and/or video files and/or image files, according to this exemplary embodiment audio files which contain telephone ringtones. The multimedia files supplied by the respective fixed-network computer 103, 104, 105 to other peer-

to-peer computers are also stored in the fixed-network
computers 103, 104, 105.

Peer-to-peer services are preferably used in accordance with
the peer-to-peer communication protocol Gnutella or the peer-
to-peer communication protocol FastTrack. If FastTrack is used
as a peer-to-peer communication protocol, then the peer-to-
peer services based upon this protocol - Imesh, Grokster or
KaZaA - are supplied, for example.

Also provided in the fixed-network communication network 101
are superpeer computers 106, 107 which have superpeer
functionality for some or all of the peer-to-peer services
available in the network, that is, serve, for example, as an
index server for a respective peer-to-peer service.

The fixed-network computers 103, 104, 105 and the fixed-
network superpeer computers 106, 107 form a so-called generic
peer-to-peer network 111, in other words a virtual network of
computers which can communicate with one another in accordance
with the respective peer-to-peer service or the respective
peer-to-peer communication protocol.

A plurality of mobile radio terminals 112 are provided in the
mobile radio communication network 102 which are likewise
configured for supplying or using peer-to-peer services.

The mobile radio terminals 112 are connected via a radio link
113 to a base station 114 and by means of this base station to
an SGSN computer 115 and via this SGSN computer to a GGSN
computer 116 so that the mobile radio terminals 112 can
exchange messages with the GGSN computer 116 in accordance
with the mobile radio protocol used in each case.

The mobile radio communication network (102) is configured in accordance with the UMTS standard.

According to this exemplary embodiment of the invention, the GGSN computer 116 serves as a mobile radio network/fixed network interface computer and is configured on the one hand for mapping a data stream incoming from the fixed-network communication network 101 to the communication protocol used in the mobile radio communication network 102 and on the other for mapping a data stream incoming from the mobile radio communication network 102 to the communication protocol used in the fixed-network communication network 101 or its data formats. Furthermore, a peer-to-peer message filter 117 is provided in the GGSN computer 116 which can detect peer-to-peer messages in the message stream which is incoming into the GGSN computer 116.

This is effected, for example, such that the peer-to-peer request message 118 supplied to the GGSN computer 116 from a mobile radio terminal 112 is supplied and unpacked in the UMTS protocol format, generally in the 3GPP protocol format used in each case, i.e. is decoded so that the peer-to-peer request message is detected in the GGSN computer 116 at the protocol level of OSI layer 7, i.e. the application layer, in accordance with the peer-to-peer communication protocol format used in each case.

Alternatively, the specification of the port via which the peer-to-peer request message 118 has been received from the GGSN computer 116 can be used as an identification criterion, since a port number is normally assigned unambiguously to a peer-to-peer service.

If the peer-to-peer request message 118 is decoded, then the
GGSN computer uses a mapping table in which all peer-to-peer
protocol formats considered by the peer-to-peer message filter
117 are specified in order to determine by comparing the
protocol formats whether and, if so, which peer-to-peer
protocol format was used in the message and which peer-to-peer
service was requested in the peer-to-peer request message 118.

If the GGSN computer 116 can detect the respective peer-to-
peer service, then it forwards the decoded peer-to-peer
request message 119 to a superpeer hosting server computer 120
connected to the GGSN computer 116. The superpeer hosting
server computer 120 is likewise disposed in the mobile radio
communication network 102. The superpeer hosting server
computer 120 receives the decoded peer-to-peer request message
119 and determines whether it can itself provide the peer-to-
peer service requested in the peer-to-peer request message 119
or not. According to this exemplary embodiment, a certain
telephone ringtone is requested by the mobile radio terminal
112 in the request message 119.

In the simplest case, it is provided that the request message
118 is not modified at all, but is only unpacked, which take
place in any case in the GGSN computer 116. This means that in
this case the peer-to-peer request message 119 is a message
sent using IP with the destination address of a random
neighboring peer.

In this case, the superpeer hosting server computer 120 is
nothing but a simple IP router computer, with the difference
that - as mentioned above - a counter mechanism is running
which ensures that, upward of a certain popularity of a

service, a superpeer instance of the respective peer-to-peer
service is installed on the superpeer hosting server computer
120.

If an unmodified version of a peer-to-peer file-sharing
program is installed on the mobile communication terminal, it
is hardly useful to achieve a situation where these request
messages are processed efficiently in the peer-to-peer message
filter 117 or the superpeer hosting server computer 120
without the peer-to-peer message filter 117 or the superpeer
hosting server computer 120 already being configured such that
it understands a basic variant of the peer-to-peer
communication protocol used, i.e. can process this protocol.
In this case, it should, depending on the peer-to-peer
communication protocol used, be ensured that
  1. a superpeer instance of the respective peer-to-peer
     service is installed (see above) and
  2. this superpeer is acquainted with the IP address of the
     superpeer hosting server computer 120 and/or the mobile
     terminals 112. The procedure is in this case protocol-
     dependent.

Provided that the superpeer selection algorithm of a certain
peer-to-peer communication protocol is sufficiently
intelligent, then after a certain time the superpeer is
automatically found in the superpeer hosting server computer
120 and made known to the mobile subscribers 112. From this
moment on, the request messages 119 will always be addressed
to the superpeer hosting server computer 120.

In aggregate, there are thus the following tasks for the peer-
to-peer message filter 117:
  1. detection of the popularity of a peer-to-peer service;

2. upward of a certain popularity of a peer-to-peer service,
   initiation of installation of a superpeer instance of
   this peer-to-peer service on the superpeer host computer
   120;
3. optionally, rejection of all messages which are not
   addressed to a superpeer instance in own network, as
   explained in detail below.

As described above, the peer-to-peer protocol messages are
already addressed to "random" IP addresses of "known" peers of
a peer-to-peer service. The peer-to-peer software determines
these known peers either with the aid of so-called rendezvous
server computers, which provide a list of "active" peers, or
from preconfigured addresses (configuration file) or from a
manual input by a user.

These three options also provide the starting points for
involving an own superpeer.

The parsing and manipulation of messages which are not
addressed to the own superpeer is very costly and is
appropriate only in exceptional cases.

Such an exceptional case is provided by redirector instances.
These are protocol-specific and roughly comparable with a
rendezvous server computer. They are also addressed directly
by peer-to-peer software on the terminal, but can, through
certain messages (protocol-specific), cause the peers to
consider superpeers.

According to the invention, the following options, among
others, thus emerge for involving an own superpeer:
   1. Rely on the intelligence of the protocol (automatic).

2. Supply rendezvous server computer with IP of own
   superpeer.
3. Provide modified versions of peer-to-peer software which
   already contain the address of own superpeer.
4. Make available on own website the address of own
   superpeer for the manual configuration of peer-to-peer
   software for downloading.
5. With the aid of redirector instances of a peer-to-peer
   service or with peer-to-peer protocol messages which
   allow a redirect to draw the attention of the peer-to-
   peer software to the own superpeer.
6. The filter rejects all messages not addressed to the
   superpeer. However, this functions only when linked with
   a method stated above for notifying the terminals of own
   superpeer.

If the corresponding peer-to-peer service is installed in the
superpeer hosting server computer 120 , then it provides the
requested peer-to-peer service and communicates to the GGSN
computer 112 the result of the requested peer-to-peer service
in a peer-to-peer response message 121. The peer-to-peer
response message 121 is transmitted to the mobile radio
terminal 112 sending the peer-to-peer request message 119. The
multimedia file specified in the peer-to-peer request message
119 can then, according to this exemplary embodiment with the
desired telephone ringtone, be read out from the memory of the
peer-superpeer hosting server computer 120 and sent to the
mobile radio terminal 112 or else be loaded from the
respective peer-to-peer server.

In this case, it is a precondition that a previously installed
and established superpeer supports a caching function and that
the desired telephone ringtone has already been requested once

and thus been cached, i.e. stored intermediately, on the
superpeer. The data transmission can thus take place. A
distinction must be made in each case between request/response
messages and the actual data exchange. In the event that the
data is not cached, the superpeer hosting server computer 120
provides only the information as to where in the peer-to-peer
network the data is to be found. The downloading is then
carried out from there.

It is in this way avoided in the above case, that a data
stream enters the fixed-network communication network 101 and
ties up resources there.

The requested peer-to-peer service is thus provided for the
mobile radio terminal 112.

It must be pointed out in this context that, according to an
alternative embodiment, the procedure described above is also
provided in the other direction of communication, namely where
there is a request message from the fixed-network
communication network to the mobile radio communication
network.

If the requested peer-to-peer service is not, however,
installed in the superpeer hosting server computer 120, then
the superpeer hosting server computer 120 forwards the request
message 119 to the fixed-network communication network 101
(not shown), i.e. the Internet or the peer-to-peer network 111
to the other fixed-network superpeer computers 106, 107 or to
the other fixed-network peer-to-peer computers 103, 104, 105
and in this way requests the peer-to-peer service for the
mobile radio terminal 109 from the fixed-network computers
103, 104, 105, 106, 107. In this case, the superpeer hosting

server computer 120 clearly represents an additional IP router computer.

Furthermore, a counter is provided in the superpeer hosting server computer 120 for each peer-to-peer service known in any way to it, which counter is increased by the value 1 upon receipt of a peer-to-peer request for the respective peer-to-peer service, provided the respective peer-to-peer service has not previously been installed on the superpeer hosting server computer 120.

If the counter value exceeds a predetermined threshold, then the peer-to-peer service thus achieving sufficient popularity is installed on the superpeer hosting server computer 120 and configured manually, preferably automatically, by means of an installation mechanism.

Upon installation of the respective peer-to-peer service on the superpeer hosting server computer 120, the service to be installed is configured in a manner and equipped with resources, for example with sufficient computing capacity, with a sufficiently fast communication link to the fixed-network communication network, i.e. one equipped with a sufficiently large bandwidth, and with sufficient memory, that the instance of the respective peer-to-peer service rises within the peer-to-peer network as a whole to become a superpeer computer.

In this context, upon installation of the peer-to-peer service on the superpeer hosting server computer 120, the service is published on correspondingly provided World Wide Web pages of a peer-to-peer service or an entry is made on rendezvous server computers or in host caches.

The mobile radio terminals 112 that want to use a certain
peer-to-peer service can also, preferably also automatically,
be informed about the existence of a superpeer instance for
the respective peer-to-peer service in the provider's own
mobile radio communication network and be configured
correspondingly.

The invention can clearly be seen as consisting in that a
superpeer computer is connected as optimally as possible to a
mobile radio communication network or is already disposed in
the mobile radio communication network 102 itself and operated
by the mobile radio network provider, so that peer-to-peer
request messages sent from a mobile radio terminal 109 are not
transmitted into the entire, principally fixed-network-based,
peer-to-peer network 111 but the messages are terminated as
early as possible, thereby reducing the data traffic that
occurs.

It should be noted in this context that the invention is
applicable both to peer-to-peer architectures comprising two
hierarchical levels and to hybrid peer-to-peer architectures
equipped with any number of additional hierarchical levels.